

Mains Circular Downlight

Downlight PAR



Downlight FAC



Downlight OFG IP44



Downlight DGC



Downlight LVR



Downlight ASYPAR



An attractive range of recessed mains downlights finished in white powdercoat. The polished aluminium reflector combined with the horizontal positioning of the single or twin fluorescent compact lamp (not included) gives excellent light distribution.

The range is designed for simple installation with a ceiling retention mechanism. The fittings can be supplied in various formats:

PAR - Open polished aluminium reflector.

FAC - Faceted open polished aluminium reflector.

OFG - Opal frosted recessed glass, IP 44 rated.

DGC - Dropped **tempered** glass cover with decorative chrome pins.

LVR - Polished aluminium six section fan louvre.

ASYPAR - Polished aluminium asymmetric version to give wall wash of light effect.

Emergency - Remote 3 hour maintained version available for the entire range. This is pre-wired to be mounted within 0.5m of the fitting. Details [here](#).

Ordering details and dimensions (mm)

Open Polished Aluminium Reflector

<u>Catalogue number</u>	<u>Lamps</u>	<u>A</u>	<u>B</u>	<u>C</u>	<u>D</u>	<u>Cut Out</u>
D1W113+/PAR	1 x 13w	285	100	195	300	175
D1W213+/PAR	2 x 13w	285	100	195	300	175
D1W118+/PAR	1 x 18w	285	100	195	300	175
D1W218+/PAR	2 x 18w	285	100	195	300	175
D1W126+/PAR	1 x 26w	325	125	225	340	205
D1W226+/PAR	2 x 26w	325	125	225	340	205
D1W132+/PAR	1 x 32w	325	125	225	340	205
D1W232+/PAR	2 x 32w	325	125	225	340	205
D1W142+/PAR	1 x 42w	325	125	225	340	205

Open Faceted Polished Aluminium Reflector

<u>Catalogue number</u>	<u>Lamps</u>	<u>A</u>	<u>B</u>	<u>C</u>	<u>D</u>	<u>Cut Out</u>
D2W113+/FAC	1 x 13w	285	100	195	300	175
D2W213+/FAC	2 x 13w	285	100	195	300	175
D2W118+/FAC	1 x 18w	285	100	195	300	175
D2W218+/FAC	2 x 18w	285	100	195	300	175
D2W126+/FAC	1 x 26w	325	125	225	340	205
D2W226+/FAC	2 x 26w	325	125	225	340	205
D2W132+/FAC	1 x 32w	325	125	225	340	205
D2W232+/FAC	2 x 32w	325	125	225	340	205
D2W142+/FAC	1 x 42w	325	125	225	340	205

Opal Frosted Recessed Glass

<u>Catalogue number</u>	<u>Lamps</u>	<u>A</u>	<u>B</u>	<u>C</u>	<u>D</u>	<u>Cut Out</u>
D3W113+/OFG	1 x 13w	285	110	195	300	175
D3W213+/OFG	2 x 13w	285	110	195	300	175
D3W118+/OFG	1 x 18w	285	110	195	300	175
D3W218+/OFG	2 x 18w	285	110	195	300	175
D3W126+/OFG	1 x 26w	325	125	230	345	205
D3W226+/OFG	2 x 26w	325	125	230	345	205

Dropped Glass Cover with Decorative Chrome Pins**

<u>Catalogue number</u>	<u>Lamps</u>	<u>A</u>	<u>B</u>	<u>C</u>	<u>D</u>	<u>Cut Out</u>
D4W113+/DGC	1 x 13w	285	100	195	300	175
D4W213+/DGC	2 x 13w	285	100	195	300	175
D4W118+/DGC	1 x 18w	285	100	195	300	175
D4W218+/DGC	2 x 18w	285	100	195	300	175
D4W126+/DGC	1 x 26w	325	130	225	340	205
D4W226+/DGC	2 x 26w	325	130	225	340	205
D4W132+/DGC	1 x 32w	325	125	225	340	205
D4W232+/DGC	2 x 32w	325	125	225	340	205
D4W142+/DGC	1 x 42w	325	125	225	340	205

**Diameter of Dropped Glass Cover is 242mm for 1 x 18w and 2 x 18w and 276mm for 1 x 26w and 2 x 26w. The drop of the glass cover is 19mm.

Polished Aluminium Six Section Fan Louvre

<u>Catalogue number</u>	<u>Lamps</u>	<u>A</u>	<u>B</u>	<u>C</u>	<u>D</u>	<u>Cut Out</u>
D5W113+/LVR	1 x 13w	285	120	195	300	175
D5W213+/LVR	2 x 13w	285	120	195	300	175
D5W118+/LVR	1 x 18w	285	120	195	300	175
D5W218+/LVR	2 x 18w	285	120	195	300	175
D5W126+/LVR	1 x 26w	325	145	230	345	205
D5W226+/LVR	2 x 26w	325	145	230	345	205

Polished Aluminium Asymmetric

<u>Catalogue number</u>	<u>Lamps</u>	<u>A</u>	<u>B</u>	<u>C</u>	<u>D</u>	<u>Cut Out</u>
D1W213/HF/ASYPAR	2 x 13w	323	161	230	359	205

+ = Control Gear options (Mouse over for legend)

HF **SS** **HF DIG DIM** **HF 1-10v DIM** **DSI and DALI dimming** **E**

Please note

TC-D lamps for Switch Start and TC-DEL lamps for 13w, 18w and 26w High Frequency and emergency. TC-TEL lamps for 32w and 42w. With Switch Start emergency conversions a single lamp Switch Start will have a TC-DEL lamp and a twin Switch Start will have one TC-D and one TC-DEL lamp.

2x18w Digital Dimming requires a remote box to house the gear.

