

# Lay-in SW T5



This new addition to our popular **LI range**, the LI SW is offered with side wings (SW).

This luminaire is available with plain or perforated (PER) panels. The side panels with prismatic cover provide side light on to the ceiling and upper walls in consideration of LG7 recommendations.

There is a choice of 3 or 4 lamps, 14W and 24W T5, with VDT louvre.

This luminaire is suitable for exposed T bar ceilings, standard or micro.

The body is manufactured from white powder coated steel. The VDT louvre is made from polished aluminium and is held in place by retaining clips enabling speedy re-lamping & routine maintenance.

**Emergency** - Three hour maintained integral emergency conversion available. Details [here](#).

Also available with high frequency digital or analogue 1-10V dimming gear to order.

## Ordering details and dimensions (mm)

<u>Catalogue number</u>	<u>Lamps</u>	<u>A</u>	<u>B</u>	<u>C</u>
LI66/314/1LV/SW/+	3 x 14w T5	595	595	60(85)
LI66/314/1LV/SW/PER/+	3 x 14w T5	595	595	60(85)
LI66/324/1LV/SW/+	3 x 24w T5	595	595	60(85)
LI66/324/1LV/SW/PER/+	3 x 24w T5	595	595	60(85)
LI66/414/1LV/SW/+	4 x 14w T5	595	595	60(85)
LI66/414/1LV/SW/PER/+	4 x 14w T5	595	595	60(85)
LI66/424/1LV/SW/+	4 x 24w T5	595	595	60(85)
LI66/424/1LV/SW/PER/+	4 x 24w T5	595	595	60(85)
<p><b>+ = Control Gear options (Mouse over for legend)</b></p> <p> <a href="#">HF</a> <a href="#">HF DIG DIM</a> <a href="#">HF 1-10v DIM</a> <a href="#">DSI and DALI dimming</a> <a href="#">E</a> </p> <p>Control gear is HF as standard.</p>				