

Recessed Lay-in SW T5

cryselco.co.uk/lis



This new addition to our popular LI range, the LI SW is offered with side wings (SW).

This luminaire is available with plain or perforated (PER) panels. The side panels with prismatic cover provide side light on to the ceiling and upper walls in consideration of LG7 recommendations.

There is a choice of 3 or 4 lamps, 14W and 24W T5, with VDT louvre.

This luminaire is suitable for exposed T bar ceilings, standard or micro.

The body is manufactured from white powder coated steel. The VDT louvre is made from polished aluminium and is held in place by retaining clips enabling speedy re-lamping & routine maintenance.

Emergency - Three hour maintained integral emergency conversion available.

Also available with high frequency digital or analogue 1-10V dimming gear to order.

SW Versions				
Cat. No.	Lamps Req	A	B	C
LI/66/314/1LV/SW/HF	3 x 14w T5	595	595	60(85)
LI/66/414/1LV/SW/HF	4 x 14w T5	595	595	60(85)
LI/66/324/1LV/SW/HF	3 x 24w T5	595	595	60(85)
LI/66/424/1LV/SW/HF	4 x 24w T5	595	595	60(85)
SW Perforated Versions				
Cat. No.	Lamps Req	A	B	C
LI/66/314/1LV/SW/HF/PER	3 x 14w T5	595	595	60(85)
LI/66/414/1LV/SW/HF/PER	4 x 14w T5	595	595	60(85)
LI/66/324/1LV/SW/HF/PER	3 x 24w T5	595	595	60(85)
LI/66/424/1LV/SW/HF/PER	4 x 24w T5	595	595	60(85)

Control Gear options
 Digital SwitchDIM dimming, Analogue 1 to 10 volt dimming, DSI and DALI, Emergency Conversion
 Control gear is HF as standard.

