

RPB T8



This is a quality recessed luminaire designed for plasterboard ceilings. The fitting can be used for most applications such as offices, schools, banks, hospitals etc as it gives quality and effective lighting. The body is made from sheet steel powder coated to RAL9003 white.

Another feature of this fitting is the generous 23mm flange to assist when the plasterboard cut out hole is covered.

Please note that this fitting is not suitable for specialist/designer ceilings such as Burgess type or concealed or exposed T bar ceilings.

Side Arm Suspensions (SAS) are included with this fitting. These fittings are not punched for Lumafix brackets.

Louvers and Metal Frames for the TP(a) Fire Rated diffusers (FFR) are fitted using 4x clamping springs for ease of use/installation which also helps save time when changing lamps and or doing any routine maintenance.

The Louvre (VDT) is specular (mirrored) aluminium. Low Brightness Aluminium Ribbed Crossblade louvers are also available (RC) to special order.

Emergency - Three hour maintained integral emergency conversion available. Details [here](#).

Ordering details and dimensions (mm)

<u>Catalogue number</u>	<u>Lamps</u>	<u>A</u>	<u>B</u>	<u>C</u>	<u>D</u>	<u>E</u>	<u>Cut Out</u>
RPB66/318/+ /++	3 x 18w	620	620	92	615	575	605x585
RPB66/418/+ /++	4 x 18w	620	620	92	615	575	605x585
RPB312/236/+ /++	2 x 36w	320	1220	92	1223	256	1180x285
RPB612/336/+ /++	3 x 36w	620	1220	92	1223	577	1180x585
RPB612/436/+ /++	4 x 36w	620	1220	92	1223	577	1180x585

+ = Control Gear options (Mouse over for legend)

HF **HF DIG DIM** **HF 1-10v DIM** **DSI and DALI dimming** **E**

++ = Louvre/Diffuser options

FFR **VDT**

