


Sedna Linkable T5



Also available in an **unlinked** variant.

How to order linkable versions:

F = First in line. Standard end cap one end and through wiring.

T = Through wiring version (order as many as required). Modified end caps are unsuitable for ends.

L = Last in line. Standard end cap one end but no through wiring as end of line.

BD = Blank Dummy available in 3 sizes, 600mm, 1200mm & 1500mm. Painted steel plate in place of louvre. Allows for through wiring only. Blank Dummies are available for twin fittings. Please enquire for single dummies.

Ordering details and dimensions (mm)

<u>Catalogue number</u>	<u>Lamps</u>	<u>A</u>	<u>B</u>	<u>C</u>
SED 312/128 T5/SATIN/LINK/ F, T or L/+	1 x 28w T5	250	1188	55
SED 312/154 T5/SATIN/LINK/ F, T or L/+	1 x 54w T5	250	1188	55
SED 315/135 T5/SATIN/LINK/ F, T or L/+	1 x 35w T5	250	1488	55
SED 315/149 T5/SATIN/LINK/ F, T or L/+	1 x 49w T5	250	1488	55
SED 312/228 T5/SATIN/LINK/ F, T or L/+	2 x 28w T5	330	1188	55
SED 312/254 T5/SATIN/LINK/ F, T or L/+	2 x 54w T5	330	1188	55
SED 315/235 T5/SATIN/LINK/ F, T or L/+	2 x 35w T5	330	1488	55
SED 315/249 T5/SATIN/LINK/ F, T or L/+	2 x 49w T5	330	1488	55
SED Twin BD 600	N/A	330	590	55
SED Twin BD 1200	N/A	330	1188	55
SED Twin BD 1500	N/A	330	1488	55

+ = Control Gear options (Mouse over for legend)

[HF](#) [HF DIG DIM](#) [HF 1-10v DIM](#) [DSI and DALI dimming](#) [E](#)

For the fixing centres of the cable supports, please enquire, as these vary between sections.

