

STM T5

STM T5 Single



STM T5 Twin



A luminaire for surface mounting complete with clear prismatic diffuser. Wired with electronic high frequency gear for T5 lamps. Body is manufactured in white powder coated steel. The diffuser is made of extruded styrene (UV stabilised).

To allow easy replacement of the tubes the polystyrene end caps are fastened by a spring.

This luminaire offers an alternative to a batten T5 with diffuser and complements our T5 range offering a more conventional look.

Please refer all 80w enquiries.

Emergency - Three hour maintained integral emergency conversion available, but some single lamp versions may have to be housed in a twin (150mm wide body) with a centrally mounted tube. Details [here](#).

Ordering details and dimensions (mm)

<u>Catalogue number</u>	<u>Lamps</u>	<u>A</u>	<u>B</u>	<u>C</u>	<u>F/C</u>
STM128 T5/+	1 x 28w T5	70	1255	70	1040
STM154 T5/+	1 x 54w T5	70	1255	70	1040
STM135 T5/+	1 x 35w T5	70	1535	70	1320
STM149 T5/+	1 x 49w T5	70	1535	70	1320
STM228 T5/+	2 x 28w T5	150	1255	70	1040
STM254 T5/+	2 x 54w T5	150	1255	70	1040
STM235 T5/+	2 x 35w T5	150	1535	70	1340
STM249 T5/+	2 x 49w T5	150	1535	70	1340

+ = Control Gear options (Mouse over for legend)

HF **HF DIG DIM** **HF 1-10v DIM** **DSI and DALI dimming** **E**

