

Surface VNS T5 IP44

cryselco.co.uk/vns



A quality surface fitting to give an attractive stylish alternative to a T5 surface fitting, with opal or clear reeded diffuser available for single or twin T5 tubes.

The diffuser is made of polycarbonate to afford extra protection and it is IP44 rated. Please note that 2x54w and 80w versions are not available due to heat build up.


14w and 24w versions are available to special order.

Emergency - integral 3 hour maintained emergency available for all ranges other than 14w and 24w.

Please refer Dimming enquiries as some units can be too lengthy to fit within the housing.

Opal Diffuser					
Cat. No.	Lamps Req	A	B	C	F/C
VNS/128/OPAL	1 x 28w T5	172	1194	53	1000
VNS/154/OPAL	1 x 54w T5	172	1194	53	1000
VNS/135/OPAL	1 x 35w T5	172	1494	53	1300
VNS/149/OPAL	1 x 49w T5	172	1494	53	1300
VNS/228/OPAL	2 x 28w T5	172	1194	53	1000
VNS/235/OPAL	2 x 35w T5	172	1494	53	1300
VNS/249/OPAL	2 x 49w T5	172	1494	53	1300

Prismatic Diffuser					
Cat. No.	Lamps Req	A	B	C	F/C
VNS/128	1 x 28w T5	172	1194	53	1000
VNS/154	1 x 54w T5	172	1194	53	1000
VNS/135	1 x 35w T5	172	1494	53	1300
VNS/149	1 x 49w T5	172	1494	53	1300
VNS/228	2 x 28w T5	172	1194	53	1000
VNS/235	2 x 35w T5	172	1494	53	1300
VNS/249	2 x 49w T5	172	1494	53	1300



Control Gear options
 Digital SwitchDIM dimming, Analogue 1 to 10 volt dimming, DSI and DALI, Emergency Conversion

