

# VNS T5

VNS T5



VNS T5 Opal



A quality surface fitting to give an attractive stylish alternative to a T5 surface fitting, with clear reeded diffuser available for single or twin T5 tubes.

The diffuser is made of polycarbonate to afford extra protection and it is IP44 rated. Please note that 2x54w and 80w versions are not available due to heat build up.

**Emergency** - integral 3 hour maintained emergency available for all ranges other than 14w and 24w. Details [here](#).

Please refer Dimming enquiries as some units can be too lengthy to fit within the housing.

Please enquire for opal or suspended versions.

## Ordering details and dimensions (mm)

<u>Catalogue number</u>	<u>Lamps</u>	<u>A</u>	<u>B</u>	<u>C</u>	<u>F/C</u>
VNS 114/+	1 x 14w T5	172	594	53	400
VNS 124/+	1 x 24w T5	172	594	53	400
VNS 128/+	1 x 28w T5	172	1194	53	1000
VNS 135/+	1 x 35w T5	172	1494	53	1300
VNS 154/+	1 x 54w T5	172	1194	53	1000
VNS 149/+	1 x 49w T5	172	1494	53	1300
VNS 214/+	2 x 14w T5	172	594	53	400
VNS 228/+	2 x 28w T5	172	1194	53	1000
VNS 235/+	2 x 35w T5	172	1494	53	1300
VNS 249/+	2 x 49w T5	172	1494	53	1300

**+ = Control Gear options (Mouse over for legend)**

**HF** **HF DIG DIM** **HF 1-10v DIM** **DSI and DALI dimming** **E**

